

CAPH.CONFIG.I18N

"i18n" sets default language string array and direction used by "language".

Contents

Methods

- [getThisLanguage](#)
- [setThisLanguage](#)
- [getNls](#)
- [setNls](#)
- [getDirRTL](#)
- [setDirRTL](#)
- [containNls](#)
- [containDirRTL](#)
- [getNlsCode](#)
- [isDirRTL](#)
- [isUseNls](#)
- [isUseDirRTL](#)

Methods

getThisLanguage	
Description	
Get the thisLanguage value.	
Parameters	■void
Return	■Array - The parent node.
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
var thisLanguage = caph.config.i18n.getThisLanguage();	
setThisLanguage	
Description	
Set the thisLanguage value.	
Parameters	■languageCode (Optional) - String - language code.
Return	■void
Emulator Support	Y

SDK Constraint	Support from version 5.1
Example	
<code>caph.config.i18n.setThisLanguage('ko');</code>	
getNls	
Description	
Get the nls value.	
Parameters	■void
Return	■Array - The parent node.
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
<code>var arrNls = caph.config.i18n.getNls();</code>	
setNls	
Description	
Set ths nls value.	
Parameters	■value - Array - language code.
Return	■void
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
<code>caph.config.i18n.setNls(['en', 'ko']);</code>	
getDirRTL	
Description	
Get the dirRTL value.	
Parameters	■void
Return	■Array - The parent node.
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
<code>var dirRTL = caph.config.i18n.getDirRTL();</code>	
setDirRTL	
Description	
Set the dirRTL value.	

Parameters	<div>■value</div> <ul style="list-style-type: none"> - Array - language code.
Return	<div>■void</div>
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
caph.config.i18n.setDirRTL(['en', 'ko']);	

containNls

Description

Check to see if value (argument) is included in nls that already set.

Parameters	<div>■value</div> <ul style="list-style-type: none"> - String - language code.
Return	<div>■Boolean</div>
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
isContainNls = caph.config.i18n.containNls('en');	

containDirRTL

Description

Check to see if value (argument) is included in dirRTL that already set.

Parameters	<div>■value</div> <ul style="list-style-type: none"> - String - language code.
Return	<div>■Boolean</div>
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	
isContainDirRTL = caph.config.i18n.containDirRTL('en');	

getNlsCode

Description

Get the nlsCode value. (By nls value, thisLanguage value)

Parameters	<div>■value (Optional)</div> <ul style="list-style-type: none"> - String - language code.
Return	<div>■String</div>
Emulator Support	Y
SDK Constraint	Support from version 5.1
Example	

```
var nlsCode = caph.config.i18n.getNlsCode();
```

isDirRTL

Description

isDirRTL is check that dirRTL is enable. (By dirRTL value, thisLanguage value)

Parameters	■value (Optional) - String - language code.
------------	---

Return	■Boolean
--------	----------

Emulator Support	Y
------------------	---

SDK Constraint	Support from version 5.1
----------------	--------------------------

Example

```
var isDirRTL = caph.config.i18n.isDirRTL();
```

isUseNls

Description

isUseNls is check that nls is enable.

Parameters	■void
------------	-------

Return	■Boolean
--------	----------

Emulator Support	Y
------------------	---

SDK Constraint	Support from version 5.1
----------------	--------------------------

Example

```
var isUseNls = caph.config.i18n.isUseNls();
```

isUseDirRTL

Description

isUseDirRTL is check that dirRTL is enable. (By dirRTL value)

Parameters	■void
------------	-------

Return	■Boolean
--------	----------

Emulator Support	Y
------------------	---

SDK Constraint	Support from version 5.1
----------------	--------------------------

Example

```
var isUseDirRTL = caph.config.i18n.isUseDirRTL();
```